

Electric scissor lifts

GS-2646 & GS-3246

MODELS	GS™-2646		GS™-3246	
	US	Metric	US	Metric
Working height maximum*	32 ft	9.92 m	38 ft	11.75 m
A Platform height maximum	26 ft	7.92 m	32 ft	9.75 m
B Platform height stowed	3 ft 9.6 in	1.16 m	4 ft 2.75 in	1.29 m
C Platform length -outside	7 ft 5 in	2.26 m	7 ft 5 in	2.26 m
extended	10 ft 5 in	3.18 m	10 ft 5 in	3.18 m
Slide-out platform extension deck	3 ft	.91 m	3 ft	.91 m
D Platform width - outside	3 ft 9.3 in	1.15 m	3 ft 9.3 in	1.15 m
Guardrail height	3 ft 7 in	1.09 m	3 ft 7 in	1.09 m
Toeboard height	6 in	.15 m	6 in	.15 m
E Height - stowed:folding guardrails	7 ft 5 in	2.26 m	7 ft 10 in	2.39 m
rails folded	5 ft 6 in	1.68 m	5 ft 11 in	1.80 m
F Length - stowed	7 ft 11 in	2.41 m	7 ft 11 in	2.41 m
extended	10 ft 10.5 in	3.31 m	10 ft 10.5 in	3.31 m
G Width	3 ft 10 in	1.17 m	3 ft 10 in	1.17 m
H Wheelbase	6 ft 1 in	1.85 m	6 ft 1 in	1.85 m
I Ground clearance - center	4 in	.10 m	4 in	.10 m
J - with pothole guards deployed	.75 in	.019 m	.75 in	.019 m

POWER			
Power source	24 V (four 6 V 225 Ah batteries)		24 V (four 6 V 225 Ah batteries)
Hydraulic system capacity	3.75 gal	14.2 L	4.5 gal 17 L

WEIGHT****			
	5,395 lbs	2,447 kg	6,200 lbs 2,812 kg

