

Narrow aisle electric scissor lifts

GS-3232

MODELS		GS™-3232	
MEASUREMENTS		US	Metric
Working height maximum*		38 ft	11.75 m
A Platform height maximum		32 ft	9.75 m
B Platform height stowed		4 ft 2.75 in	1.29 m
C Platform length - outside		7 ft 5 in	2.26 m
extended		10 ft 5 in	3.18 m
Slide-out platform extension deck		3 ft	.91 m
D Platform width - outside		2 ft 8 in	.81 m
Guardrail height: fixed rails			
fold down rails (CE)		3 ft 7 in	1.10 m
Toeboard height		6 in	.15 m
E Height - stowed			
fixed rails			
folding guardrails (CE)		8 ft	2.43 m
rails folded		6 ft 8 in	2.03 m
F Length - stowed		8 ft	2.43 m
Length - extended		10 ft 11 in	3.33 m
G Width		2 ft 8 in	.81 m
H Wheelbase		6 ft 1 in	1.85 m
I Ground clearance - center		3.5 in	.09 m
J - with pothole guards deployed		.75 in	.02 m

PRODUCTIVITY			
Maximum platform occupancy**		2	2
Lift capacity		500 lbs	227 kg
Extension deck capacity		250 lbs	113 kg
Drive height		22 ft	6.71 m
Drive speed - stowed		2.2 mph	3.5 km/h
Drive speed - raised		0.5 mph	0.8 km/h
Gradeability - stowed***		25%	
Maximum outrigger leveling: front to back		3°	
side to side		5°	
Turning radius - inside		zero	zero
Turning radius - outside		7 ft	2.13 m
Raise / lower speed		57 / 40 sec	57 / 40 sec
Controls		proportional	
Drive		dual front wheel	
Multiple disc brakes		dual rear wheel	
Tyres - solid non-marking		15 x 5 x 11 in	38 x 13 x 28 cm
WEIGHT****			
		5,185 lbs	2,352 kg

